Rhodes Canyon Landfill Inspection Form Post Closure Care Monitoring of the Soil Cover

Inspections during the post closure care period are to occur semi-annually and shall include, at a minimum, each of the areas listed below. Specific information can be found in the CMI Work Plan for Rhodes Canyon Landfill (WSMR-14, SWMU 114 &115) Report No. WS-ES-EC-0311. Copies of this inspection form are to be kept in a bound notebook located at the WS-ES library and the WTS office.

Date of Inspection:	8-22-12	Inspector:	Brad	ley Davis
			Yes	No
deterioration? 5. Inspected landfill cov 6. Inspected surroundir erosion which may ir	lock present? Indinspected for breaches of the control of the cont	ge? cessive		
	· · · · · · · · · · · · · · · · · · ·		Satisfactory	Unsatisfactory
5. Fence in condition a. Fence b. Gates c. Signs d. Fence clear of tr	ash		र्यार्थान	
Groundwater monito a. Wells locked b. Concrete pad co c. Well covers tight	ndition		र्यास्	
vegetation such desirable)	\mathcal{A} . D		TE TENTE E	
Re-inspection date, if	necessary:			

Rhodes Canyon Landfill Inspection Form Post Closure Care Monitoring of the Soil Cover

Date of Inspection: 8-22-12 Inspector: Bradley Davis)
Comments: riks forming on borrow pit - slope.	
Minor vills on Cap Some burrowing.	
Fence in good condition. Veretation looks -good.	,
Fence in good condition. Vegetation looks -good. Some erosion along sides of Channels (rocklined)	
Actions Taken: Récommend - fixes to Cap following MONS Season - Cover sills to Keep from forming gullies ON No Slope of borrow pit and on sap. Fillin burrows	. <u>88</u> 7
38ason - Covel 1145 to Keep from formin gullies ON 110	17 M
Slope of borrow fit and on rap. tillin burrows	

- ✓ All unsatisfactory observations are to be immediately reported to the WSMR Environmental Services Division.
- ✓ All unsatisfactory observations must be fixed and re-inspected within 30 days. Zfa
- ✓ One copy of this inspection form will be maintained in bound notebook at ₩75 office for three years from the date of inspection.
- ✓ One copy of this inspection form shall be kept on file with the WSMR Environmental Services Division for the remainder of the post-closure care period.
- Cap and well repairs will be conducted with the same materials and construction techniques used during the initial construction. Any modifications to these techniques or materials must be approved in writing by the NMED-HWB.

